

551, 531

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau(43) International Publication Date  
28 October 2004 (28.10.2004)

PCT

(10) International Publication Number  
**WO 2004/091799 A1**(51) International Patent Classification<sup>7</sup>:  
F01M 13/04, B01D 45/14

B04B 5/12,

(72) Inventor; and

(75) Inventor/Applicant (for US only): ELIASSON, Thomas  
[SE/SE]; Hyltingevägen 29, S-125 40 Älvsjö (SE).

(21) International Application Number:

PCT/SE2004/000401

(74) Agent: CLIVEMO, Ingemar; Alfa Laval Corporate AB,  
Hans Stahles väg, S-147 80 Tumba (SE).

(22) International Filing Date: 18 March 2004 (18.03.2004)

(81) Designated States (unless otherwise indicated, for every  
kind of national protection available): AE, AG, AL, AM,  
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,  
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,  
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,  
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,  
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,  
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,  
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,  
ZW.

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

0301140-0

16 April 2003 (16.04.2003)

SE

0302463-5


16 September 2003 (16.09.2003)

SE

(71) Applicant (for all designated States except US): ALFA  
LAVAL CORPORATE AB [SE/SE]; Rudeboksvägen 3,  
S-221 00 Lund (SE).(84) Designated States (unless otherwise indicated, for every  
kind of regional protection available): ARIPO (BW, GH,  
GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),

[Continued on next page]

(54) Title: AN APPARATUS FOR CLEANING OF A GAS



(57) Abstract: In an apparatus for cleaning of a gas a centrifugal rotor (5) is rotatable in a separation chamber (4) about a vertical rotational axis (R). The centrifugal rotor (5) is rotatable by means of a turbine wheel (20) arranged in a drive chamber (19) situated below the separation chamber (4). The centrifugal rotor (5) and the turbine wheel (20) are connected with each other by means of a shaft (6). The separation chamber (4) and the drive chamber (19) are separated from each other by two partitions (11, 12), through which the shaft (6) extends and which between themselves form a drainage chamber (23). A nozzle (21) is arranged to spray a liquid against the turbine wheel (20) in the drive chamber (19) for rotation thereof and of the centrifugal rotor (5). The drainage chamber (23) has an outlet (31) for draining of liquid having entered the drainage chamber from the drive chamber (19), so that liquid shall not be able to flow from the drive chamber (19) to the separation chamber (4).

WO 2004/091799 A1



Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

**Published:**

— *with international search report*